

- Standard Features
- Options
- Technical Data

1,000 - 20,000
BTUH

400 Volt
Air Conditioners

ICEqube

Standard Features

- Digital temperature controller with alarm
- Built-in condensate evaporator
- Durable 16 gauge welded steel construction
- Efficient, quiet, long lasting rotary compressor
- Environment friendly HFC refrigerant
- Easy pull-out filter
- Space saving aesthetic cabinet design
- Designed to mount on side of enclosure while maintaining NEMA type 12, 3R, 4, or 4X integrity



Options & Accessories

- Stainless Steel
- Remote Controller Kit
- Replacement Filters
- Corrosive Packages
- Crankcase Heater
- Low Ambient
- External Heat Output
- Internal Heat Output
- Alarm Output

Technical Data

Model	BTUH	Volts Hz	Max Amps	Weight (lbs.)	Dimensions
IQ1000V	1000	400/60/50	0.9/1.0	51	17.31"Hx14.41"Wx8.03"D
IQ2500V	2500	400/60/50	2.0/2.2	86	32.53"Hx19.25"Wx6.38"D
IQ3500V	3500	400/60/50	2.5/2.7	86	32.53"Hx19.25"Wx6.38"D
IQ4500V	4500	400/60/50	2.6/2.9	86	32.53"Hx19.25"Wx6.38"D
IQ10000V	10000	400/60/50	4.5/5.0	173	57.65"Hx17.65"Wx10.34"D
IQ12000V	12000	400/60/50	5.6/6.2	173	57.65"Hx17.65"Wx10.34"D
IQ14000V	14000	400/60/50	6.6/7.2	232	56.00"Hx20.06"Wx14.31"D
IQ17000V	17000	400/60/50	8.9/9.8	232	56.00"Hx20.06"Wx14.31"D
IQ20000V	20000	400/60/50	10.0/11.0	232	56.00"Hx20.06"Wx14.31"D
IQ1200VS	1200	400/60/50	1.0/1.2	56	26.28"Hx11.51"Wx6.26"D
IQ1500VS	1500	400/60/50	1.1/1.2	56	26.28"Hx11.51"Wx6.26"D
IQ1800VS	1800	400/60/50	1.2/1.3	56	26.28"Hx11.51"Wx6.26"D
IQ2200VS	2200	400/60/50	1.9/2.1	70	34.12"Hx12.27"Wx6.34"D
IQ3000VS	3000	400/60/50	2.0/2.2	70	34.12"Hx12.27"Wx6.34"D
IQ4000VS	4000	400/60/50	2.4/2.7	76	34.12"Hx12.27"Wx8.34"D
IQ5500VS	5500	400/60/50	2.5/2.8	91	34.12"Hx12.27"Wx10.39"D
IQ6000VS	6000	400/60/50	2.3/2.5	93	34.12"Hx12.27"Wx10.39"D
IQ5000V16	5000	400/60/50	2.4/2.6	105	40.10"Hx15.93"Wx7.34"D
IQ6000V16	6000	400/60/50	2.5/2.7	105	40.10"Hx15.93"Wx7.34"D
IQ8000V16	8000	400/60/50	3.9/4.3	130	46.15"Hx15.93"Wx10.34"D
IQ1200VXS	1200	400/60/50	1.0/1.2	59	34.00"Hx6.50"Wx11.50"D
IQ1500VXS	1500	400/60/50	1.1/1.2	59	34.00"Hx6.50"Wx11.50"D
IQ1800VXS	1800	400/60/50	1.2/1.3	59	34.00"Hx6.50"Wx11.50"D
IQ2000VXS	2000	400/60/50	2.0/2.2	74	28.03"Hx10.00"Wx10.00"D
IQ2400VXS	2400	400/60/50	2.0/2.2	74	28.03"Hx10.00"Wx10.00"D
IQ4000VXS	4000	400/60/50	2.6/2.9	133	40.03"Hx11.05"Wx15.00"D
IQ5000VXS	5000	400/60/50	2.7/3.0	133	40.03"Hx11.05"Wx15.00"D
IQ6000VXS	6000	400/60/50	2.8/3.1	133	40.03"Hx11.05"Wx15.00"D
IQ4000V16HA*	4000	400/60/50	2.2/2.5	105	46.15"Hx15.93"Wx10.34"D
IQ5000V16HA*	5000	400/60/50	3.8/4.2	130	46.15"Hx15.93"Wx10.34"D
IQ6000V16HA*	6000	400/60/50	4.0/4.4	130	46.15"Hx15.93"Wx10.34"D
IQ8000VHA*	8000	400/60/50	4.5/4.9	173	57.65"Hx17.65"Wx10.34"D

Ice Qube, Inc., 141 Wilson Ave., Greensburg, PA 15601

Call: (724) 837-7600

Fax: (724) 837-3386

Visit: www.IceQube.com

Email: sales@IceQube.com