

- Standard Features
- Options
- Technical Data

1,000 - 20,000  
BTUH

480 Volt  
Air Conditioners

ICEqube

### Standard Features

- Digital temperature controller with alarm
- Built-in condensate evaporator
- Durable 16 gauge welded steel construction
- Efficient, quiet, long lasting rotary compressor
- Environment friendly HFC refrigerant
- Easy pull-out filter
- UL Listed
- Space saving aesthetic cabinet design
- Designed to mount on side of enclosure while maintaining NEMA type 12, 3R, 4, or 4X integrity



### Options & Accessories

- Stainless Steel
- Remote Controller Kit
- Replacement Filters
- Corrosive Packages
- Crankcase Heater
- Low Ambient
- External Heat Output
- Internal Heat Output
- Alarm Output

### Technical Data

Model	BTUH	Volts Hz	Max Amps	Weight (lbs.)	Dimensions
IQ1000V	1000	480/60/50	0.8/0.9	51	17.31"Hx14.41"Wx8.03"D
IQ2500V	2500	480/60/50	1.7/1.9	86	32.53"Hx19.25"Wx6.38"D
IQ3500V	3500	480/60/50	2.1/2.3	86	32.53"Hx19.25"Wx6.38"D
IQ4500V	4500	480/60/50	2.3/2.5	86	32.53"Hx19.25"Wx6.38"D
IQ10000V	10000	480/60/50	4.0/4.4	180	57.65"Hx17.65"Wx10.34"D
IQ12000V	12000	480/60/50	4.9/5.4	232	57.65"Hx17.65"Wx10.34"D
IQ14000V	14000	480/60/50	5.7/6.3	232	56.00"Hx20.06"Wx14.31"D
IQ17000V	17000	480/60/50	7.8/8.6	232	56.00"Hx20.06"Wx14.31"D
IQ20000V	20000	480/60/50	8.7/9.6	232	56.00"Hx20.06"Wx14.31"D
IQ1200VS	1200	480/60/50	0.9/1.0	56	26.28"Hx11.51"Wx6.26"D
IQ1500VS	1500	480/60/50	0.9/1.0	56	26.28"Hx11.51"Wx6.26"D
IQ1800VS	1800	480/60/50	1.0/1.1	56	26.28"Hx11.51"Wx6.26"D
IQ2200VS	2200	480/60/50	1.6/1.8	70	34.12"Hx12.27"Wx6.34"D
IQ3000VS	3000	480/60/50	1.6/1.8	70	34.12"Hx12.27"Wx6.34"D
IQ4000VS	4000	480/60/50	2.1/2.3	76	34.12"Hx12.27"Wx8.34"D
IQ5500VS	5500	480/60/50	2.1/2.3	92	34.12"Hx12.27"Wx10.39"D
IQ6000VS	6000	480/60/50	1.9/2.1	93	34.12"Hx12.27"Wx10.39"D
IQ5000V16	5000	480/60/50	2.1/2.3	105	40.10"Hx15.93"Wx7.34"D
IQ6000V16	6000	480/60/50	2.2/2.4	105	40.10"Hx15.93"Wx7.34"D
IQ8000V16	8000	480/60/50	3.4/3.7	130	46.15"Hx15.93"Wx10.34"D
IQ1200VXS	1200	480/60/50	0.9/1.0	59	34.00"Hx6.50"Wx11.50"D
IQ1500VXS	1500	480/60/50	0.9/1.0	59	34.00"Hx6.50"Wx11.50"D
IQ1800VXS	1800	480/60/50	1.0/1.1	59	34.00"Hx6.50"Wx11.50"D
IQ2000VXS	2000	480/60/50	1.6/1.8	74	28.03"Hx10.00"Wx10.00"D
IQ2400VXS	2400	480/60/50	1.7/1.9	74	28.03"Hx10.00"Wx10.00"D
IQ4000VXS	4000	480/60/50	2.3/2.5	133	40.03"Hx11.05"Wx15.00"D
IQ5000VXS	5000	480/60/50	2.4/2.6	133	40.03"Hx11.05"Wx15.00"D
IQ6000VXS	6000	480/60/50	2.6/2.9	133	40.03"Hx11.05"Wx15.00"D
IQ4000V16HA*	4000	480/60/50	1.8/2.0	130	46.15"Hx15.93"Wx10.34"D
IQ5000V16HA*	5000	480/60/50	3.2/3.5	130	46.15"Hx15.93"Wx10.34"D
IQ6000V16HA*	6000	480/60/50	3.4/3.7	130	46.15"Hx15.93"Wx10.34"D
IQ8000VHA*	8000	480/60/50	3.9/4.3	180	57.65"Hx17.65"Wx10.34"D

\*Designed for High Ambient Application