



IQ6000V16
COOLING CAPACITY: 6000 BTUH (1760W) @131°F (55°C)
MAXIMUM AMPS: 10.5 (1260W) @120V/60HZ
MAXIMUM AMPS: 5.2/5.8 (1196/1276W) @230/220V 60/50HZ
MAXIMUM OPERATING TEMP: 131°F (55°C)
MINIMUM OPERATING TEMP: -4°F (-20°C)
DIMENSIONS: 35.97" (914MM) H X 15.93" (405MM) W X 7.34" (186MM) D
WEIGHT: 105 LBS (47.7KG)

							ITEM NUMBER N/A	USED ON IQ6000V16		UNLESS OTHERWISE SPECIFIED TOLERANCES X ±.060 .XX ±.030 .XXX ±.015 FRACTIONAL ±1/16 ANGULAR ±1/2° SURFACE FINISH 63		ICE QUBE, INC. THIS IS A PROPRIETARY DOCUMENT. DO NOT REPRODUCE OR DISCLOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF ICE QUBE, INC.	
							MATERIAL N/A			DESCRIPTION IQ6000V16 SPEC DRAWING XP2		DRAWING NUMBER IQ351383	
C	ADDED CFM, dBA, AND CLEARANCE INFO					RCC	3/23/2018					REV	
B	ADDED WATTAGE INFO					RCC	12/18/2017						
A	REDRAWN IN SW					RCC	4/4/2017						
REV	REVISION					CHG	DATE	APP	DATE	CN #		C	



EVAP. OUTLET ≈ 236 CFM
COND. OUTLET ≈ 410 CFM
SOUND LEVEL @5FT FROM UNIT @ A HT. OF 3FT = 66 dBA
SOUND LEVEL @2FT FROM UNIT @ A HT. OF 5FT = 64 dBA
CONDENSER INLET MIN. CLEARANCE 2.34"



ITEM NUMBER <i>N/A</i>		USED ON <i>IQ6000V16</i>		UNLESS OTHERWISE SPECIFIED TOLERANCES X ±.060 .XX ±.030 .XXX ±.015 FRACTIONAL ±1/4 ANGULAR ±1/2°		ICE QUBE, INC. THIS IS A PROPRIETARY DOCUMENT. DO NOT REPRODUCE OR DISCLOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF ICE QUBE, INC.	
MATERIAL <i>N/A</i>				SURFACE FINISH 63		DESCRIPTION <i>IQ6000V16 SPEC DRAWING XP2</i>	
EST WT: lbs		DRAWN BY <i>RCC</i>		DATE <i>4/4/2017</i>		DRAWING NUMBER <i>IQ351383</i>	
		SCALE <i>1:6</i>		DO NOT SCALE DRAWING DIMENSIONS ARE INCHES		REV <i>C</i>	