


SHEET 1 of 2



IMPORTANT
GASKET MUST BE APPLIED AS SHOWN FOR PROPER
OPERATION AND TO MAINTAIN ENCLOSURE INTEGRITY

EVAP. OUTLET ≈ 510 CFM
COND. OUTLET ≈ 800 CFM
SOUND LEVEL @5FT FROM UNIT @ A HT. OF 3FT = 68 dBA
SOUND LEVEL @2FT FROM UNIT @ A HT. OF 5FT = 70 dBA
CONDENSER INLET MIN. CLEARANCE 3.00"

ITEM NUMBER <i>N/A</i>		USED ON <i>IQ8000EVZ2</i>		UNLESS OTHERWISE SPECIFIED TOLERANCES X ±.060 .XX ±.030 .XXX ±.015 FRACTIONAL ±1/4 ANGULAR ±1/2° SURFACE FINISH 63		ICE QUBE, INC. THIS IS A PROPRIETARY DOCUMENT. DO NOT REPRODUCE OR DISCLOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF ICE QUBE, INC.	
MATERIAL <i>N/A</i>		SCALE 1:5		DRAWING NUMBER <i>IQ351311</i>		DESCRIPTION <i>IQ8000EVZ2 ZONE 2 ATEX IECEx SPEC DRAWING</i>	
EST WT: lbs		DATE 1/19/2017		REV <i>E</i>			
DRAWN BY <i>ART</i>							