




IQ8000V16  
COOLING CAPACITY: 8000 BTUH (2346W) @131°F (55°C)  
MAXIMUM AMPS: 3.4/3.7 (1632/1776W) @480V/60/50HZ  
MAXIMUM OPERATING TEMP: 131°F (55°C)  
MINIMUM OPERATING TEMP: -4°F (-20°C)  
DIMENSIONS: 46.16" (1172MM) H X 15.93" (405MM) W X 10.34" (263MM) D  
WEIGHT: 150 LBS (68.2KG)

ITEM NUMBER							USED ON		UNLESS OTHERWISE SPECIFIED TOLERANCES		ICE QUBE, INC.	
N/A							IQ8000V16		.X ±.060 .XX ±.030 .XXX ±.015		THIS IS A PROPRIETARY DOCUMENT. DO NOT REPRODUCE OR DISCLOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF ICE QUBE, INC.	
MATERIAL							EST WT: lbs		FRACTIONAL ±1/16 ANGULAR ±1/2°		DESCRIPTION	
N/A							DRAWN BY		DATE		SCALE	
RCC							4/14/17		1:11		SURFACE FINISH	
DO NOT SCALE DRAWING DIMENSIONS ARE INCHES							DRAWING NUMBER		REV		C	
C							ADDED CFM, dBA, AND CLEARANCE INFO		RCC		3/29/2018	
B							ADDED 50HZ AND WATTAGE INFO		RCC		12/15/2017	
A							REDRAWN IN SW		RCC		4/14/2017	
REV							REVISION		CHG		DATE	
							APP		DATE		CN #	



ITEM NUMBER N/A		USED ON <i>IQ8000V16</i>		UNLESS OTHERWISE SPECIFIED TOLERANCES .X                      ±.060 .XX                    ±.030 .XXX                  ±.015		 <b>ICE QUBE, INC.</b> <small>THIS IS A PROPRIETARY DOCUMENT. DO NOT REPRODUCE OR DISCLOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF ICE QUBE, INC.</small>	
MATERIAL N/A				FRACTIONAL ANGULAR            ±1/4 ±1/2		DESCRIPTION <i>IQ8000V16 SPEC DRAWING, 480V XP2</i>	
EST WT:                      lbs				SURFACE FINISH 		DRAWING NUMBER <i>IQ320100</i>	
DRAWN BY <i>RCC</i>		DATE <i>4/14/17</i>		SCALE <i>1:7</i>		REV <i>C</i>	
				DO NOT SCALE DRAWING DIMENSIONS ARE INCHES			